



# ALMA 64-antenna Correlator Status and VLBI Compatibility

Alain Baudry

Univ. Bordeaux, OASU/LAB & European ALMA Project Office, ESO

*'mm-VLBI with ALMA and Other Telescopes, Scientific Workshop'*


*June 27-28, 2012, ESO*



# Contents

## ***ALMA 64-antenna correlator***

- Very brief history
- Main Specifications
- Status
- VLBI compatibility





# 64-antenna Correlator / History

- Development began at NRAO with pure XF architecture
- Evolved into a digital hybrid XF system to include the core of the 2GC study in Europe
  - FXF architecture
  - Digital filter cards with 32 frequency mobile sub-bands
  - Filter outputs sent to 32 correlator planes



# Deliverables

- 4 independent Quadrants of hardware
  - Each Qt. processes a 2GHz pair for up to 64 antennas
  - Modularity for commissioning
- Working internal hardware and firmware
- Additional important hardware
  - Custom Test Fixtures (Filter and Correlator cards) for maintenance/repair in addition to embedded testing
  - Two 2-antenna correlators at OSF
- Documentation




# Main Specifications

## 64-antenna correlator


- **Antennas** 64 (2016 pairings + 64 auto-correl.)
- **Input / Output sample format** 3-bit ADC / 2- or 4-bit correlation
- **Baseband per antenna** 4 x 2 GHz x 2 polars. (8 BBs)
- **Polarization products** 1, 2 or 4
- **Max baseline delay range** 30 km (up to 300km)
- **Processing rate** 125 MHz
- **Hardware correlators / baseline** 32 klags & 32 kleads
- **Max spectral resol. & Channels** 3.8 kHz, 8192 channels

- \* **Min. accumulation time** 16 ms cross-correl. & 1 ms auto-correl.
- \* **Subarraying** up to 6
- \* **Phased array outputs** VLBI
- \* **Output rate 2GByte/s per Qt.** ALMA system supports 60 MByte/sec peak  
Routine operation, ~25% peak rate or ~50GByte/hour



**Correlator Block Diagram**  
(Baudry 2009, The Messenger, vol 135)





# Status (1)

- *Hardware and Firmware complete and verified for all elements in correlator*
- *Operational software first used in system testing at integration center prior to shipping to AOS*
  - Close cooperation with ALMA Computing



# Status (2)

32 racks in 4 Quadrants

*First Quadrant* installed at AOS in October 2008

*Second & third Quadrants* installed in 2009 & 2010

*2-quadrant operation in routine use* for CSV & Early Science

all BB pairs for up to 32 antennas

*Fourth Quadrant*

at AOS, testing on-going, final acceptance-on-site meeting by mid-July

*Migration to 4-Quadrant configuration and testing finished by the end of Sept* ... can process up to 64 antennas

*4-Quadrant operation ready for ES well before Cycle 1 starts*

# One Quadrant




## Complete Correlator System, 32 racks in 4 Quadrants

- ~2600 printed circuit boards total in system
- ~20 million solder joints
- 8192 Altera Stratix II FPGAs (90 nm technology) in TFB cards
- 32768 custom correlator chips
- 64-antenna Correlator is a highly specialized computing system  
 $1.7 \times 10^{16}$  operations/sec (multiply-and-add calculations)

# Correlator room at AOS, 5000m

32 Station & Correlator racks in 4 Qts.



- **Power <150 kW** including control & computing racks
- Heat dissipation was a challenge (board and system level)



# Overview of Spectral Capabilities

- Two categories of Observing Modes

## *Frequency Division Mode (FDM)*

2 GHz BB divided into 32 sub-bands (digital hybrid architecture)

- Adequate for **spectroscopy** (high resolution)

## *Time Division Mode (TDM)*

correlator behaves as an XF machine

- Adequate for **continuum sources** or **broad spectral emission**

- 67 modes validated by Correl IPT

Small subset of modes offered for Early Science



# Phasing up the Array

**All basic requirements to phase up the array are in place in 64-antenna Correlator**

- Analog sum FPGAs on correlator cards to compute sums of antenna signals
- TFB cards already have phase adjust capability with digital LO for each of 32 sub-bands
- Power capacity sufficient to add up VLBI mode
- Unused space in correl. racks to include the additional cards for interfacing to fibers & VLBI terminal




# Phasing up the Array & VLBI

- Details on how to close the overall « phasing loop » still to be investigated in depth (software mainly)
- Data processing route for VLBI observing once phase corrections are known
  - TFB phase adjusted outputs => passed to Correl cards which output antenna sums (mask selectable set of antennas) => PIC card (Phasing Interface Card) ... new interface card connected to Fiber and VLBI Terminal
- Main function of PIC (new card for Correlator)
  - Format the data into packets for 10Gb ethernet
  - Being developed at NRAO with PIC Test Fixture
  - 2 cards per Qt.




# Data processing & PIC Test Fixture




# Digital Tunable Filter Bank (TFB)

*Phase shift and Gain* (tot power) controlled from/to SCC  
Firmware implemented in TFB



# Phasing Interface Card



Modified Final Adder Board

